

- Each sheet is unique because of the organic involvement during the creation process, expect the patina to evolve over time.
- Sheet size is 48" x 96" or 48" x 120"
- Approximate weight is 2.5 lbs/SF
- Sheets are 16 gauge (.059"/1.5 mm thick)
- When cutting, it is recommended that a very sharp saw or shear be used. Due to the organic nature of the metal base, some lifting of the edges of the top coat may occur when shearing. This can be remedied by using a utility/hobby knife with a fresh blade at a sharp angle.
- Forming to a 90° angle is not recommended as the finish may craze at the bend.
- Care should be taken during handling and installation to prevent oils from hands or other sources from coming in contact with the finish. Gloves are recommended.
- In the event that Black Organic becomes scratched, the silver-colored base material may be exposed. A matte black touch up could be applied to disguise the scratch without disturbing the organic aesthetic.

Installation Options

- **Standard Gage E (Extrusion)** – Gage will powder coat extrusion in a coordinating low sheen black
- **Stand-Offs** – By contractor
- **Direct Glue** – Use appropriate commercial grade construction adhesive to mount to surface (i.e. sheetrock, MDF, or other)
- **Column Covers** – Black Organic can be roll formed for a minimum 12" diameter
- Water jet cutting and roll forming are just a couple of the ways Black Organic can be customized by the contractor.

